



DIY Retail Roll

(2200 and 2500 Series)

rFOIL™ Applications:

- General Residential Projects
- Do It Yourself Projects
- Cottages and RV's
- Improving Current Insulation Value

rFOIL™ Insulates:

- Walls
- Ceilings
- Crawl spaces
- Basements
- Metal Roofs
- Pipes
- Sheds and much more

rFOIL™ Benefits:

- Staple Tabs for Between Joists
- Minimal Product Thickness
- Easy to Handle and Install
- Vapor Barrier Protection
- Increases Insulating Value of
- Wall Systems



rFOIL™ DIY rolls are multi-purpose insulation that come in convenient DIY sizes. These smaller rolls are ideal for small scale jobs; just buy what you need. rFOIL™ retail rolls are available in the following configurations.

Reflective/Bubble/Reflective is a single or double layer of polyethylene bubbles bonded to and sandwiched between two layers of metalized foil sheets.

Reflective/Bubble/POLY is a single or double layer of polyethylene bubbles sandwiched between a layer of metalized foil sheet and a layer of white polyethylene.

PATENTED

(See website for details)

www.rFOIL.com



FEATURES

Metalized Foil / Double Bubble/ Metalized Foil

- Achieve higher comfort
- Reflects 96% of radiant heat that accounts for 75% of heat loss
- Reduce radiant heat loss
- Lowers utility costs

POLY / Double Bubble / Metalized Foil

- More aesthetically pleasing
- Provides efficient insulation
- Maintains a comfortable climate in your building
- Product thickness matching the industry standard

BENEFITS

PRODUCTS




AVAILABLE IN:

- Single or Double Bubble
- Square Edge, Tab 1 Side, Tab 2 Sides, Quick Seam Adhesive Strip

Description	Size
R / DB / R or R / DB / P	24" x 10'
R / DB / R or R / DB / P	48" x 10'
R / DB / R	16" x 25'
R / DB / R or P / DB / R	24" x 25'
R / DB / R or P / DB / R	48" x 25'
R / DB / R or P / DB / R	24" x 50'
R / DB / R or P / DB / R	48" x 50'

SPECIFICATIONS

Physical Properties	Test	Poly / Double Bubble / Reflective Foil P / DB / R	Reflective Foil / Double Bubble / Reflective Foil R / DB / R
NOMINAL THICKNESS	—	5/16"	5/16"
FIRE RATING	ASTM E84-09	CLASS 1 / CLASS A	
EMISSION	ASTM C1371-04A	0.04	0.04
REFLECTIVITY	ASTM E903	0.96	0.96
WATER VAPOR PERMEABILITY	ASTM E96	0.12 Perms	0.02 Perms
RESISTANCE TO FUNGI & BACTERIA	ASTM C1149	DOES NOT PROMOTE GROWTH	
PLIABILITY	ASTM C1224-03	NO CRACKING	
BLEEDING AND DELAMINATION	ASTM C1224-03	NO BLEEDING OR DELAMINATION	
CORROSIVENESS	ASTM D3310-00	PASSES	
FIRE RATING - FULL ROOM BURN TEST	NFPA 286	PASSES	



Warranty, Specific Applications and Installation Guides can be found on our Applications Manuals or at www.rfoil.com

rFOIL™ Code Compliance
International code council
(ICC) report ESR-1236

The above report has been issued based on rfoil compliant with the below codes:

- 2009 International Building Code (IBC)
- 2009 International Residential Code (IRC)
- 2009 International Mechanical Code (IMC)
- 2009 International Energy Conservation Code (IECC)
- 1997 Uniform building code (UBC)



279 Humberline Drive Etobicoke, ON M9W 5T6
Call Toll Free: 1-800-837-8961 Fax: 416-798-1342
Email: sales@rfoil.com Website: www.rfoil.com